



									
40...400 Hz	VA (1)	VA (1)	U _n	gG	40...400 Hz	VA (1)	VA (1)	U _n	gG
LC1 F115/150					LC1 F185/225				
LX9 FF042	690	6,6	42V	10A	LX9 FG042	950	8,9	42V	16A
LX9 FF048			48V	8A	LX9 FG048			48V	10A
LX9 FF110			110/115V	4A	LX9 FG110			110/115V	6A
LX9 FF127			127V	4A	LX9 FG127			127V	6A
LX9 FF220	855	8,1	220/230V	2A	LX9 FG220	1180	10,9	220/230V	4A
LX9 FF240			240V	2A	LX9 FG240			240V	4A
LX9 FF380			380/400V	2A	LX9 FG380			380/400V	2A
LX9 FF415			415/440V	1A	LX9 FG415			415/440V	2A
LX9 FF500			500V	1A	LX9 FG500			500V	2A

(1) 50/60 Hz, θ = 20 °C

The following products meet the Energy Efficiency requirements.
 The power consumption and the Energy Efficiency grades are:
 以下型号产品符合能效要求，产品的吸持功率和能效等级分别如下：

Product Type 产品型号	LC1F115 LC1F150	LC1F185 LC1F225 LC1F265 LC1F300 LC1F400 LC1F500 LC1F630 LC1F1250
Maximum power consumption lower than 最大吸持功率低于 (VA)	51.3	91.2
Energy efficiency grade 能效等级	2	2

	200V - 208V	220V - 240V	460V - 480V	575V - 600V	SCCR	Type J Fuse Ampacity Maximum
Contactor	HP	HP	HP	HP	KA	A
LC1F115	30	40	75	100	100	200
CR1F150/LC1F150	40	50	100	125	100	200
CR1F185/LC1F185	50	60	125	150	100	400
CR1F265/LC1F265	60	75	150	200	100	600
LC1F330	75	100	200	250	100	600